




DESCRIPTION	FKAT2WT-E-2TON	FKAT2WT-E-3TON	FKAT2WT-E-5TON	FKAT2WT-E-9TON	FKAT2WT-E-10TON
Dimensions externes (mm)	2435 x 1219 x 457	2435 x 1828 x 610	3048 x 1828 x 610	3658 x 1828 x 610	3962 x 2134 x 610
Epaisseur ridelles	2/3 mm (tôle profilée)		3 mm (tôle profilée)		
Pneus	6.00x16, 7.50x16, 9.00x16			7.50 x 16, 9.00 x 16, 12.5/80-15.3 & 400/60-15.5 (14 à 18 PR)	
Essieu (mm)	65x65/75x75		75x75	90x90	100x100
Poids (Kg. Approx.)	600	1014	1180	1553	1820
Ressort à lame (Option)	36"		42"		
Puissance requise (CV)	20-35	30-50	50-70	70-90	90-120



Pneus larges pour une meilleure stabilité et adhérence




Béquille à vis pour le stationnement



Essieu renforcé



Moyeu robuste



Cylindre hydraulique télescopique



Tôle profilée résistante



Centre de gravité bas



Barre d'attelage détachable pour augmenter la capacité



Feux de route protégés pour plus de sécurité

